

vnir

CASI-1500

Airborne Hyperspectral Solutions.



Wide Array VNIR Imager
Programmable, Up to 288 Bands
40 degree FOV, 1500 Spatial Pixels
0.38 - 1.05 micron Spectral Range
Diffraction Limited Optics



CASI-1500

Sensor Type

VNIR Pushbroom Sensor (Compact Airborne Spectrographic Imager)

Performance

Spectral Range (Continuous Coverage)	380-1050nm
# Spectral Channels	Up to 288
# Spatial Pixels	1500
Total Field of View	40 degrees
IFOV	0.49 mRad
f/#	f/3.5
Spectral Width Sampling/Row	2.4nm
Spectral Resolution (FWHM)	<3.5nm
Pixel Size	20x20 microns
Dynamic Range	14-bits (16384:1)
Data Rate, Sustained	9Mpix/sec
Spectral Smile/Keystone Distortion	±0.35 pixels
Peak Signal to Noise Ratio (SNR)	SNR models for various radiance conditions are available from ITRES

Dimensions, Weights, and Power

Item	Dimensions (cm)	Weight (kg)
SHU	W 47.0 H 46.7 D 53.5	25
ICU (Single)	W 48.3 H 17.8 D 52.3	16
15" Display	W 41.0 H 30.9 D 6.52	8
Power	24-32VDC 13.5A (Typical)	

Environmental Constraints

Operating Temperature	Ambient 0 to +35°C (+32 to +104°F) RH 20-80% non-condensing
Maximum Altitude	3,048 m (10,000 ft) ASL (unpressurized, non-condensing environment)
Storage Temperature	Optimum -20 to +60°C (-4 to +120°F) RH 10-90% non-condensing

Operation

Display	15" sunlight readable, 1024x768 resolution.
Operator Control	Via keyboard, Windows™ OS
Real-Time Display	Scene image, diagnostics, signal level display
Remote Diagnostics	Ethernet-ready remote diagnostic capability on ICU
Data Storage	Swappable mass storage

Data Processing System

- Processing software Linux and Windows-based
- Playback software (Quicklook)
- Generates 16-bit BIP format data compatible with ENVI (BIL, BSQ formats possible)
- ASCII format ancillary QC data output - clocking, attitude, logging, GPS, and sensor health monitoring information
- Outputs diagnostic information
- Selectable band output

Geocorrection System

- GPS/IMU processing
- Data synchronization (GPS, attitude, and image streams)
- After bundle adjustment no need for GCPs
- Stabilized mount option

Geocorrection/Orthorectification Software

- Best nadir pixel selection function during mosaicking
- Accepts Lidar, Ifsar, and USGS DEM inputs
- Nearest neighbor algorithm used - maintains radiometric fidelity
- Separately stores ancillary data (e.g. pointing vector, DEM)

Spatial Resolution & Flight Altitude

- Across-track spatial resolution depends on flight altitude
For example, if 1 m pixels are desired, then flight altitude = 2060 m AGL
- Along-track pixel dimension depends on frame rate and aircraft speed (frame rate with the CASI depends on the number of bands acquired)
For example, if 1 m pixels are desired and flight speed is 120 knots, 36 spectral bands may be acquired. At 90 knots, 48 bands are possible.

All ITRES sensors are calibrated to traceable standards.
Specifications subject to change without notice. ©2008 ITRES Research Limited