



# Antcom's **G5 Antenna**, Active **L1/L2 Glonass + L1/L2 GPS + OmniStar** Antenna, P/N: G5Ant-52AT1 **Survey Mount Configuration** **(with Filters, better RTK Performance, Optimized for L1/L2 Glonass & L1/L2 GPS & OmniStar)**



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . http://www.antcom.com

**NOTICE OF PROPRIETARY RIGHTS**  
THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY FORBIDDEN UNLESS YOU AGREE THAT ITS USE IS LIMITED TO USE WITH YOUR COMPANY ONLY AND DOES NOT INCLUDE REPRODUCTION, OR PROCESSING, AND OTHER USE AS SPECIFICALLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

**REVISIONS**

ZONE	REV	DESCRIPTION	DATE	APPROVED
		ECO# 0020, RELEASE	Mar-24-09	S. HUYNH

**SPECIFICATIONS**

**ELECTRICAL:**

	L5 GPS E5, E5a, E5b Galileo L5 IRNSS	L2 GPS B2 Compass	L2 GLONASS E6 Galileo B3 Compass	OmniSTAR / L-Band L6 Galileo B1 Compass	L1 GPS E1, E2 Galileo L1 IRNSS	L1 GLONASS
<b>FREQUENCY:</b>	1176.45 ± 12 MHz 1164.45 - 1219.14 MHz 1176.45 ± 15 MHz	1227.60 ± 12 MHz 1207.14 ± 10 MHz	1252.50 ± 7.5 MHz 1266.75 - 1290.75 MHz 1268.52 ± 10 MHz	1542.50 ± 14.0 MHz 1542.50 ± 5.0 MHz 1561.098 ± 10 MHz	1575.42 ± 15.0 MHz 1575.42 ± 17.0 MHz 1575.42 ± 12.0 MHz	1609 ± 7.0 MHz
<b>RADIATION PATTERN:</b>	RHCP		RHCP		RHCP	
<b>POLARIZATION:</b>	< 2.0:1	< 2.0:1	< 2.0:1	< 2.0:1	< 2.0:1	< 2.0:1
<b>VSWR:</b>	50 ohms					
<b>IMPEDANCE:</b>	50 ohms					
<b>ANTENNA GAIN (dBi):</b>	HEMISPHERICAL					
@ 90° (ZENITH):	- 1	+ 5.3	+ 2.8	+ 2.8	+ 4.9	+ 4.7
@ 10° Elevation:	- 9	- 2.7	- 5.2	- 6.0	- 3.8	- 4.2
@ 20° Elevation:	- 7	- 0.9	- 3.6	- 4.2	- 2.1	- 2.3
@ 30° Elevation:	- 6	+ 0.4	- 2.4	- 2.4	- 0.3	- 0.6
@ 60 - 90° Elevation:	> - 3	> 4.2	> 1.6	> + 1.3	> + 3.4	> + 3.2
<b>BEAM WIDTH (3dB):</b>	85 Deg.	90 Deg.	90 Deg.	80 Deg.	80 Deg.	82 Deg.
<b>AXIAL RATIO:</b>	1.5 dB	1 dB	1 dB	3 dB	1 dB	4 dB
<b>LIGHTNING PROTECTION:</b>	DC GROUNDING					
<b>LNA GAIN:</b>	35 dB	35 dB	35 dB	33 dB	33 dB	33 dB
<b>LNA NOISE FIGURE:</b>	3.0 dB	3.0 dB	3.0 dB	3.0 dB	3.0 dB	3.0 dB
<b>LNA P1dB Out:</b>	+13 dBm	+13 dBm	+13 dBm	+13 dBm	+13 dBm	+13 dBm
<b>LNA DC POWER:</b>	2.5V/20mA, 3V/29mA, 3.3V/35mA, (2.5-24)V/<50mA					
<b>POWER HANDLING:</b>	1 Watt CW, Optional: 10 Watts 1 Microsec Pulse (-AL-)					

**MECHANICAL:**

**SIZE:** DIAMETER: 5.00 in. [127.00 mm]  
HEIGHT: 1.68in [42.7mm]; 0.457in. [11.6 mm] Above G.P.

**WEIGHT:** 7oz. (199 g)

**FINISH:** SKYDROLRESISTANTPOLYURETHANENAMEL  
BASE IRIDITE PER MIL-C-5541FCLASS 1A

**MATERIAL:** 6061-T6ALUMINUMALLOYBASE  
COMPOSITE RADOME,IMPACT, ABRASION,UV, SOLVENT,  
SKYDROLRESISTANCE AND FIRE RETARDANT

**CONNECTOR:** TNC FEMALE CONNECTOR  
(OPTION: SMA, BNC, TNC Bulkhead, N,  
N Bulkhead, MCX, MMCX)

**ENVIRONMENTAL:**

**TEMPERATURE:** -67 °F TO +185 °F [-55 °C TO +85 °C]  
70,000ft.

**VIBRATION:** > 30 G's  
HERMETICALLYSEAL

**FEDERAL & MILITARY SPECIFICATIONS**

FAA TSO-C144, DO-160D, DO-228, MIL-C-5541,  
MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

**ACCEPTANCE TEST PROCEDURE** ATP-GPS-L1L2-100

**DC GROUNDING**

**CONNECTOR:** TNC FEMALE CONNECTOR  
(OPTION: SMA, BNC, TNC Bulkhead, N,  
N Bulkhead, MCX, MMCX)

**P/N: G5Ant-52AT1**

SIZE	LNA	CABLE LENGTH	CONNECTOR	COLOR
1.2" SQ.	42: ARINC743	X: NO CABLE	S: SMA; SMB; SMBR; B: BNC	-1: GLOSSWHITE#17925PER FED-STD-595B
1.9" 1.9" SQ.	52: 2.6" DIA. ON 5" GROUNDPLANE		M: MCX; MMB; MMCX; MMR; MMCX-R	-2: LUSTERLESS GRAY#36320PER FED-STD-595B
2.6" DIA.	72: 7" DIA. CHOKERING		N: N; NB: N-Bulkhead	-3: OLIVE DRAB GREEN#34094PER FED-STD-595B
3.3" DIA.	5: Bare on 5in [128mm] Dia. GroundPlane		T: TNC; TB: TNC-Bulkhead	-4: LUSTERLESS BLACK#37038PER FED-STD-595B
4: MINI ARINC	X.X: Bare on X.Xin Dia. GroundPlane		SMC, SSMC, SMB, SSMMA	

QUANTITY REQD	DESCRIPTION	PARTS LIST	PART NO	FINISH	ITEM NO
1	5/8"-11 Mount		MTR-3B-G5	-	1